

Appln. No. 10/660,543
Amendment Dated March 21, 2005
Reply to Office action of February 16, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): An apparatus for measuring the relative position of a movable object, said apparatus comprising:
a member movable along a path corresponding to the position of the object;
a plurality spaced electrical contacts insulated from one another and positioned along said path;
data-storing means operatively connected to said plurality of contacts, said data-storing means including for storing a corresponding plurality of memory locations each of which stores a preset, different position measurement data and each of which is respectively operatively connected to one of said plurality of contacts at a corresponding plurality of memory locations, each of said position measurement data stored respectively in said plurality of memory locations being uniquely respectively associated with one of said plurality of contacts along said path to which said memory location is operatively respectively connected; and
output means operatively connected to said data storing means;
said movable member being effective when in engagement with one of said contacts to cause only the data stored in the one of said memory locations then operatively connected to said one of said contacts to be applied to said output means.

Claim 2 (previously presented): The apparatus of Claim 1, in which said output means is a display device.

Claim 3 (previously presented): The apparatus of Claim 1, in which said output means is a CPU.

Claim 4 (previously presented): The apparatus of Claim 1, in which said contacts are arranged in an arcuate path.

Claim 5 (previously presented): The apparatus of Claim 4, in which said movable member is connected at one of its ends to a voltage source and its other free end is movable along said arcuate path to make electrical contact with one of said contacts.

Claim 6 (previously presented): The apparatus of Claim 1, in which said contacts are arranged in a rectilinear path.

Claim 7 (previously presented): The apparatus of Claim 6, in which said member is movable axially along said rectilinear path for making contact with aligned pairs of said contacts at each of its ends.

Claim 8 (previously presented): The apparatus of Claim 1, in which said data-storing means is a ROM.

Claim 9 (previously presented): The apparatus of Claim 1, further comprising a voltage source, said member being effective when in electrical contact with one of said contacts to place an associated one of said memory locations in a circuit arrangement with said voltage source.

Claim 10 (previously presented): The apparatus of Claim 9, in which said output means is a display device.

Claim 11 (previously presented): The apparatus of Claim 9, in which said output means is a CPU.

Claim 12 (previously presented): The apparatus of Claim 9, in which said contacts are arranged in an arcuate path.

Claim 13 (currently amended): The apparatus of Claim 12, in which said movable member is connected at one of its ends to said voltage source and its other free end is movable along said arcuate path to make electrical contact with one of said contacts.

Claim 14 (previously presented): The apparatus of Claim 9, in which said contacts are arranged in a rectilinear path.

Claim 15 (previously presented): The apparatus of Claim 14, in which said member is movable axially along said rectilinear path for making contact with along pairs of said Contacts at its ends.

Claim 16 (previously presented): The apparatus of Claim 9, in which said data-storing means is a ROM.

Claim 17 (currently amended): A method for determining the relative position of a movable object, said method comprising the steps of:
arranging a plurality of fixed, spaced and insulated electrical contacts along a path;
moving an electrically conductive member along said path by an amount representative of the relative movement of said object, thereby causing said movable member to make electrical contact with one of said contacts;

storing respectively a corresponding plurality of different preset position data in a corresponding plurality of data-storing locations in a memory respectively operatively connected to said plurality of contacts, the position data stored in said plurality of data-storing locations being respectively uniquely associated with one of said plurality of contacts; and causing the position data stored in the one of said data-storing locations associated with and electrically operatively connected to the said one of said plurality of contacts then contacted by said movable member to be applied to an output device.